

Our solution to slow drains

Easy to use, **e_z Clean Drains** leads the new generation of drain maintenance products

Good drain management practices accumulate over time — so do bad ones. **e_z Clean Drains** reverses the buildup of old food particles, soap film, body oils, fat, grease and organic oils reviving your drains to their natural free flowing state.

e_z Clean Drains specially formulated blend of surfactants and 100% active enzymes work together to excite the existing bacteria to degrade buildup so it cannot reform.

With regular use, **e_z Clean Drains** prevents foul odors from occurring and safeguards you against slow-drain syndrome.

- Effective disposal cleaner and deodorizer
- Non-toxic, non-corrosive
- Neutralizes odors
- Minimizes drain backups
- Beneficial for septic system
- Caustic and phosphate free
- Safe for all sink finishes, drains and pipes

GLB Incorporated
13916 Leetsbir Rd.
Sturtevant, WI 53177

Phone: 800-236-1366
E-mail: info@glakes.net

e_z Clean Drains



e_z



e_z Clean Drains

Usage Recommendations

Directions

All Floor Drains: 2 ounces per quart of warm water per floor drain

Initial Treatment – use 1 quart of mixture 5 days in a row

Maintenance Treatment – use 1 quart of mixture once weekly

Commercial / Industrial: 2 ounces per quart of warm water per drain

Initial Treatment – use 1 quart of mixture 5 days in a row

Maintenance Treatment – use 1 quart of mixture once weekly

Residential / Hotel: 1 ounce per quart of warm water per drain

Initial Treatment – use 1 quart of mixture 3 days in a row

Maintenance Treatment – use 1 quart of mixture once weekly

For Optimum Results

- Run warm water for 60 seconds before pouring down the drain.
- Maintenance treatment is to be done at closing or low-flow period.
- Use more frequently for slow drains or for excess grease in drainline.
- Clean with **e_z Clean Floors**, **e_z Clean Hard Surface** or any of our other **e_z Clean** drain and pipe-friendly products.

Technical Specs

pH Range: 3.25–4.20

Fragrance: None added

Appearance: Translucent amber liquid

Packaging, Handling and Storage

Size	Pkg	Dimensions (LxWxH)	Weight
1-gal	4/cs	15" x 10" x 10"	39 lbs
5-gal	pail	12" x 10" x 15"	48 lbs
55-gal	drum	24" dia. x 36" H	475 lbs

Store this product out of direct sunlight in a cool dry area. For best results, use within 12 months. Request an **e_z Clean Drains** MSDS for more specific information.

Disclaimer

This information is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. GLB, Incorporated assumes no responsibility for personal injury or property damage to the Vendee, Users or Third Parties caused by the material. Such Vendees or Users assume all risks associated with the use of this material. The contents of this document are subject to change without notice.

GLB Incorporated

13916 Leetsbir Rd.
Sturtevant, WI 53177

Phone: 800-236-1366

E-mail: info@glakes.net