

Our powerful, skid-free, floor cleaner

Effective economical, **e_z Clean Floors** keeps on cleaning

e_z Clean Floors provides the solution to today's floor care needs. This new product is designed for everyday use on ceramic, vinyl, hardwood, concrete or any water-safe surface.

e_z Clean Floors outperforms standard chemical cleaners by breaking down surface grease and grime on contact. Long after the initial application, cleaning continues at the molecular level enabling floors to be kept cleaner longer.

By removing embedded soil from floor surface pores, grout and cracks, **e_z Clean Floors** regularly controls the source of obnoxious odors and reduces workplace floor slippage.

- Continuous cleaning action at work
- Leaves no residue for high gloss
- Naturally eliminates odors
- No special equipment required
- Designed for daily industrial use
- Safe for all water-safe surfaces

e_z Clean Floors



GLB Incorporated
13916 Leetsbir Rd.
Sturtevant, WI 53177

Phone: 800-236-1366
E-mail: info@glakes.net

e_z



e_z Clean Floors

Usage Recommendations

Floor Type

Ceramic Tile or Hardwood: 2 ounces per gallon of water
Allow 5 minutes contact time. Mop or clean as usual.

Vinyl: 1 ounce per gallon of water
Use a mop or clean as usual. Rinse if necessary.

Concrete: 2 – 4 ounces per gallon of water
Allow 1 – 5 minutes of contact time. Use a scrub brush or mop.

Mechanical Floor Cleaner: 1 – 3 ounces per gallon of water
Follow floor cleaning machine instructions.

For Optimum Results

- Mix with warm water when cleaning.
- Increase contact time to enhance product performance.
- Apply multiple times for old or heavy build-up.
- Use a scrub brush to achieve a deeper clean.
- Rinse with clean hot water as needed.

Technical Specs

pH Range: 3.25–4.20
Fragrance: None added
Appearance: Translucent amber liquid

Packaging, Handling and Storage

Size	Pkg	Dimensions (LxWxH)	Weight
1-gal	4/cs	15" x 10" x 10"	39 lbs
5-gal	pail	12" x 10" x 15"	48 lbs
55-gal	drum	24" dia. x 36" H	475 lbs

Store this product out of direct sunlight in a cool dry area. For best results, use within 12 months. Request an e_z Clean Floors MSDS for more specific information.

Disclaimer

This information is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. GLB, Incorporated assumes no responsibility for personal injury or property damage to the Vendee, Users or Third Parties caused by the material. Such Vendees or Users assume all risks associated with the use of this material. The contents of this document are subject to change without notice.

GLB Incorporated
13916 Leetsbir Rd.
Sturtevant, WI 53177

Phone: 800-236-1366
E-mail: info@glakes.net